

—
SYSTEMS
—

nexTER


TITUS®

AT THE LEADING EDGE FOR HIGH INTENSITY
AND COMPLEX MISSIONS



CREATING NEW REFERENCES IN DEFENSE

nexTER 
A COMPANY OF

TITUS®

—
SYSTEMS
—

**AT THE LEADING EDGE FOR HIGH INTENSITY
AND COMPLEX SECURITY MISSIONS**

TITUS® is our latest generation 6x6 armoured vehicle. It offers a wide response to all asymmetric threats: mobility, protection, ergonomics, flexible deployment. TITUS® is the 21st century versatile vehicle. It brings NEXTER technological touch in the heart of action.



TITUS[®]

TURNING CIRCLE BETWEEN
KERBS ADAPTED TO URBAN
ENVIRONMENT (13M)



PLATFORM

- Combat and fire support APC, Command Post, Engineer, Anti tank missile, Mortar (81mm, 120mm).

MISSIONS

- Conventional warfare
- Counter terrorism
- Combat in built up area
- Peace enforcement
- Border control

MOBILITY

- TATRA – T815 chassis
- Turning circle between kerbs adapted to urban area
- Significant payload growth potential
- COTS maintenance and reliability
- Obstacle clearance
- Rapid acceleration and efficient braking

PROTECTION

- Ballistic: Evolutive from level 2, NEXTER RPG protection
- Mine protection: up to 4a/4b
- IED: up to 150kg

HUMAN INTEGRATION

- Tactical pivoting seat in front vision and optimized collaborative dialogue with the squad
- Hatches, rear ramp and side doors for easy ingress/egress
- Large interior volume for personnel equipment storage
- Perimeter vision

FIRE POWER

- from 7.62mm up to 25mm
- 40mm grenade launcher

HIGH TECH EQUIPMENT

- Recce UGV (Nexetr Nerva LG Robot...)
- BMS
- Jammers, shot detectors, additional equipment
- Day/night sights, perimetric vision

TITUS® | FEATURES AND SPECIFICATIONS

Weight And Dimensions

Unladen weight: 17t
Operational weight: 23t
Maximum gross weight: 27t
Width: 2.55m
Height: 2.73 m (roof)
Length: 7.77 m
Ground clearance: 0.3/0.4/0.5m

Protection

Standard:

- Ballistic level: 2 to 4
- Mines level: 3A/3B until 4A/4B
- IED blast: from 50 to 150kg

Higher levels upon request

Mobility

Engine: 500HP
Running gear: Semi-independent stub axle.
Tyres: Michelin 16.R20, SYEGON® CTIS and flat-running system
Steering: Steering axle # 1 and 3. Turning circle: 13m

Performance

Range: 700km
Maximum speed: 110km/h
Slope: 60%
Step: 700mm
Ground clearance: 450mm
Side slope: 30%
Fording: 1.2m without preparation

Human Integration

Crew: 3+10 or 2+12 depending on configuration
Interior volume: 14.4m³
Storage capacity: 2.4m³ inside, 1.5m³ outside
Ramp and openable side doors
6 front side windows and roof hatches

Outside Vision

One front windscreen and two side windows (transparent armour)
One rear ramp window with firing port
Three side windows on each side in the rear compartment (option)

Liveability

Air conditioning / heating system (weather conditions A1/C0/C1 optional)
Air renewal: 240m³/h
Full NRBC (as optional)

Energy

Four AGM 12V – 120Ah batteries
One alternator delivering 370A

Fire power

RWS 7.62 mm up to 25 mm
Grenade launcher 40 mm



www.nexter-group.fr

All data and information presented in this document is the property of Nexter-Group. This document is disclosed for information purposes only. Nexter Systems reserves the right to change the specifications without prior notification.
Nexter Systems - 13 route de la Minière - 78034 Versailles Cedex.

nexter **K+N**
A COMPANY OF **D+S**